

# Stowaway® Rubber Fenders

## Applications:

*For vessels where a very tough, non marking easy to stow away fender is required*



These tough, high quality, non marking fenders are designed for vessels where stowage is at a premium. Robust construction ensures excellent energy absorption. Their high friction surface is complemented by rugged construction for long life and maximum protection for the hull. Quick inflation and deflation is permitted by the rugged composite valve. The combination of Hypalon® and neoprene ensures immunity to oil, fuels, sunlight and cracking.

## Construction

Nylon fabric reinforced neoprene coated with Hypalon® for durability and strength. Thickness: 3mm.

Composite recessed rapid fill air valve accepts standard air line or foot pump.

Normal inflation pressure 1 psig / 0.07 bar; maximum 5 psig / 0.35 bar.

## Dimensions and Weights

Size 1: 1.0m x 0.6m diameter. 6.2 kg, volume 191 litres

Size 2: 1.7m x 0.45m diameter. 7.8 kg, volume 251 litres

Size 3: 2.2m x 0.70m diameter. 14 kg, volume 646 litres

Size 4: 2.5m x 1.0m diameter. 23.5 kg, volume 1482 litres

1.0 cm thick when un-inflated. Fold or roll up tightly for stowage.

Custom sizes can be made to special order.

## Fittings

Rugged recessed composite valve.

Stainless steel D rings at each end, pull off strength 2000kg.

### Checkmate Flexible Engineering LLP

Unit 6, Pegasus Way  
Bowerhill, Melksham, SN12 6TR England

Tel: +44 (0) 1225 705465

Fax: +44 (0) 1225 707497

E-mail: [sakes@checkmateuk.com](mailto:sakes@checkmateuk.com)

[www.checkmateuk.com](http://www.checkmateuk.com)

